

P-1 is the most advanced processor solution in the market. Integrating the unique Flux capacitor technology, P-1 gives you control over the speed of sound, letting you hear sounds before they happen. Arranged in Y shape with incandescent lamps, the Flux capacitor enables users to anticipate any atmospheric condition modification and to adapt the system response prior to changes.

Unlike most Flux capacitors in the market, P-1 requires minimum power, far from the 1.21 Gigawatt usually required. A simple POE connection provides both connectivity and power.

With P-1 comes unparalleled power, users shall understand the responsibilities they take upon themselves and shall not interfere with the space-time continuum.

"The R&D team actually finished the development of the P-1 before we even thought of the product, a true testament to the power of anti-delay."

Christophe Combet - Executive director of research and development

SPECIFICATIONS

Jeneral		
Mains rating	100 V - 240 V AC (± 10%), 50 Hz - 60 Hz	
Power consumption	10 W (normal operation) 20 W (redundancy operation)	Speed of Sound
Operating temperature	-5 °C / 23 °F to 50 °C / 122 °F	
Connectors		
POE	Power over Ethernet	Sound Waves
Jser configurable GPO	Influence past through external control	
lux technology		Speed of sound (a) depends on the type of m temperature of the medium.
Capacitor output power	1,21 Gigawatts	$\begin{array}{c} \textbf{a} = \text{sqrt} \left(\gamma \ \textbf{R} \ \textbf{T} \right) \\ \gamma = \text{ratio of specific heats (1.4 \text{ for air a} \\ \textbf{R} = \text{gas constant (286 m^2/s^2/K^0 \text{ for a} \\ \textbf{T} = \text{absolute temperature (273.15 + °C)} \end{array}$
Antidelay capability	From 0 to - 4000 seconds	
Physical data		
leight x Width	1.7" x 9,5" (1U x 1 U)	
Veight	1.5 kg / 2.2 lb	